

Wireless Electronic Handle

EH4W

Now every Fieldpiece accessory head can be read wirelessly, from up to 75' away.

- 5000 count display
- 75' wireless signal
- Sends and receives wireless measurements
- Use with any Fieldpiece Accessory Head
- ET2W also sold separately



EH4W

ET2W
Included

Electronic Handle for Accessory Heads

EHDL1

Converts any Fieldpiece Accessory Head into a standalone instrument.

- MIN/MAX button
- Use with any Fieldpiece Accessory Head
- Hold button



Current Clamp Head

ACH4

- Measures AC Amps from 1A to 400A
- Accuracy:
1A-20A AC: $\pm(1.5\% \text{ rdg} + 0.2A)$
20A-100A AC: $\pm(2.5\% \text{ rdg} + 0.3A)$
100A-400A AC: $\pm(3.5\% \text{ rdg} + 0.5A)$
- .91" (23mm) maximum conductor diameter



600A AC/DC Current Clamp

ACDC6

Connect to any DMM with industry standard jacks and mV ranges to measure AC or DC current up to 600A. Jaw opens to 1.18".



Silicone Test Leads

ASLS2

- High copper strands, silicone insulated test leads
- Basket style strain relief



Deluxe Silicone Test Leads

ADLS2

- Same as the ASLS2 with the addition of removable probe tips for connection to accessory heads



Deluxe Test Lead Kit

ADK7

- Silicone test leads, removable probe tips and alligator clips for grounding
- Includes molex tips



Dual Alligator Clips

ADA2

- Red and black vinyl insulated cables with small alligator clips on the ends. Each shorting cable is 3.5 feet long



Flame Diode Test Adapter Kit

AQK3

- DMM jack to quick-connect for flame diode test
- Quick connect to mini-plug adapter



Accessory Head Adapter

AHDL1

The AHDL1 connects Fieldpiece Accessory Heads to classic digital multimeters with mV ranges (AC and DC).

