

# Eaton DPF222R

Catalog Number: DPF222R

Eaton air conditioning disconnect, Fused pullout, 60A, 120/240V, 10 kAIC, #14-3 Cu/Al 60°C or 75°C, NEMA 3R Galvanized Steel enclosure, 3 hp at 120V, 10 hp at 240V, ANSI 61 gray

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton air conditioning disconnect	DPF222R
<b>UPC</b>	<b>Product Length/Depth</b>
782114166932	5.4 in
<b>Product Height</b>	<b>Product Width</b>
8.7 in	3.15 in
<b>Product Weight</b>	<b>Warranty</b>
2.7 lb	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
<b>Certifications</b>	<b>Catalog Notes</b>
CSA Certified UL Listed	For replacement pullout head, order part number 96-3258-4.



## Product specifications

### Enclosure material

Galvanized steel

### Interrupt rating

10 kAIC

### Type

Fused pullout

### Wire size

#14-3 AWG Cu/Al

### Horsepower

3 hp at 120 V, 10 hp at 240 V

### Color

ANSI 61 gray

### Enclosure

NEMA 3R

### Voltage rating

120/240 V

### Amperage Rating

60A

## Resources

### Brochures

[Air Conditioning Disconnects](#)

### Catalogs

[Eaton's Volume 1—Residential and Light Commercial](#)

### Drawings

[Dimensional Drawing - SKT 200A 1P HCP](#)

### Specifications and datasheets

[Eaton Specification Sheet - DPF222R](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)