

| | SPECIFICATION SHEETS |
|--------|-------------------------|
| NAME: | CL110 LED |
| TYPE: | LOW PROFILE FLUSH MOUNT |
| DATE: | |
| NOTES: | |

SPECIFICATIONS


| WIRING: | Installs easily in traditional junction boxes (3" or 4"). | |
|-------------|---|--|
| OPTICS: | LED technology delivers 1000 lumens (7" version) and 2000 lumens (11" version). | |
| ELECTRICAL: | Energy efficient LED utilizing a 120V 60Hz driver. | |
| | ETL and Energy Star listed to U.S. and Canadian safety standards for DAMP & WET locations. | |
| | Phase Control: Forward Phase | |
| LENS: | LED technology in combination with a white acrylic frosted lens, provides an even light distribution. | |

| COLOR TEMPERATURE: | 3K - 4K |
|---------------------------------|-------------------|
| OPERATING TEMPERATURE: | -40°C + 40°C |
| CRI: | 80+ |
| LUMEN OUTPUT: | 2000 lumens |
| DIMMABLE: | Yes |
| WATTS: | 26 W |
| LED LIFE: | 50,000 hours |
| WARRANTY: | 5 years |
| VOLTAGE: | 120V |
| DIAMETER: | 11.00" (279.4 mm) |
| HEIGHT: | 1.70" (43.2 mm) |
| INTEGRATED MOTION SENSOR: | No |

APPLICATIONS

The Aura low-profile series LED flush mounts provide general illumination suitable for indoor or outdoor residential and commercial applications. Ideal for use in closets, foyers, hallways, bedrooms, offices, utility work areas, stairways, and many other rooms in the house or work place environment.

DIMENSIONS



RATINGS









ORDERING GUIDE

AURA CL110 SERIES

 Series
 Color Temperature
 Finish

 CL110-26W
 3K 3000K/80CRI/26W
 WH White

4K 4000K/80CRI/26W

Notes: Configure product using BOLD options: Ex: CL110-26W-3K-WH