

Project Name

Location

Prepared By



Notes

[www] 12-11-2023 01:20:12

General

| | |
|-------------------------|--------------------------------|
| Status | Active |
| Watts | 38W |
| Incandescent Equivalent | 150W |
| Volts | 120V-277V |
| Ballast Type | Type B |
| Shape | T8 |
| Base | Recessed Double Contact HO/VHO |
| ANSI Base | R17d |
| Nominal Length | 96 |
| Finish | White |
| CCT (Kelvin) | 4000K/5000K/6500K |
| Temperature | Cool White to Daylight |
| CRI | 83 |
| Lumens | 5400L/5500L/5300L |
| Beam Spread | 180 |
| Hours Rated | 50000 |
| Lamp Type | Linear |
| Technology | LED |

Electrical

| | |
|-------------------------|----------------------------|
| Ballasting Requirements | Ballast Bypass |
| Operating Frequency | 50/60Hz |
| Power Factor | 0.9 |
| THD | <25% |
| Operating Temperature | -20C (-4F) to +45C (+113F) |

Physical

| | |
|---------------|-----------------|
| MOL | 94 |
| MOD | 1 |
| Material | Glass / Plastic |
| Lens Finish | Frost |
| Lens Material | Glass |
| Housing Color | White |

Additional Information

| | |
|----------------------------|---|
| Includes | Each master case contains a 10 pack of item 80-984 (LED T8 Support Clip.) |
| Shatter-Proof Type | PET Coated |
| Rated For Enclosed Fixture | Yes |
| Warranty | 5 Year Limited - T8 LED Bulbs - Ballast Bypass |

Compliance

| | |
|------------------------|--|
| Safety Listing | cRUus - Recognized Component; ETLus - Listed; cULus - Classified |
| Location Rating | Damp |
| Energy Star | No |
| DLC Approved | No |
| CA T20 / T24 Rationale | Exempt - Base Not Regulated |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| RoHS Compliant | Yes |

| | |
|---------------|----------|
| FCC Compliant | Yes |
| NSF Approved | Yes |
| SDS Sheet | LED_Lamp |

Copyright 2023 Satco Products, Inc.
All Rights Reserved

For More Information Visit:
<https://www.satco.com/>

