



GOLIATH® CONDENSATE PANS AND RISERS

Goliath®

Secondary Drain Pans

Code	Pan Size	Outer (Max) Dimension			Inside (Drip Area) Dimension		
		Length	Width	Depth	Length	Width	Depth
96200	26x56"	56.625"	26.5"	2.75"	51.0"	19.5"	2.0"
96202	28x57"	57.25"	28.375"	5.25"	51.75"	21.5"	2.0"
96204	28x69"	69.125"	28.25"	4.25"	66.5"	26.0"	2.0"
96206	30x50"	50.50"	30.25"	4.00"	45.25"	22.75"	2.1"
96208	30x62"	63.00"	30.375"	4.25"	56.875"	22.75"	2.1"
96210	30x66"	66.50"	30.25"	4.00"	64.00"	22.75"	2.1"

FEATURES

- Hangable
- Extreme temperature durability
- High tensile strength
- Crack/split/leak/rust resistant
- Self extinguishing

US Patent
7,900,795



Application • Goliath Series Secondary Drain Pans are the strongest, most rugged HVAC secondary drain pans on the market today • Made With Pride from our own patented blend of advanced polymer DexElar® material, Goliath Series Secondary Drain Pans are engineered with superior one piece structural strength to produce a nearly indestructible drain pan with rolled edges and no seams • Each pan is strong enough to hang using only one pair of steel support struts, ensuring a quick-and-easy professional installation

- Features a network of built-in risers, which are compatible with a wide variety of sizes of HVAC units and eliminate the need to shop around for additional risers or mounting blocks. Some Goliath pans have lower risers when space is restricted • Risers run the length of pan for better strength when hanging • Each pan has specially designed indentations for placement of hanging brackets
- Goliath Series Secondary Drain Pans are compatible with our AG-4200 Condensate Management System water sensor and drain adapter as well as AG-GFR Vibration Isolators to quiet any noisy HVAC unit.

All pans meet or exceed all international building codes and come with a 10 Year Limited Warranty.