

**NIBCO**

1516 Middlebury Street

Elkhart, IN 46516-4740

**Phone:** 574.295.3000 • **Fax:** 800.234.0557**E-Mail:** [info@nibco.com](mailto:info@nibco.com) • **Web site:** [www.nibco.com](http://www.nibco.com)**Material Number NLG100K, LD-2000 Butterfly Valve - Ductile Iron, Lug Type, 200 PSI, Handle**

The NIBCO® ductile iron lug butterfly valve provides ease of operation with quarter-turn (90 degrees) open to close. With the internal stem/disc geometric drive design, there is no need for pins or bolts that may create leak paths or turbulence in the waterway. An extended neck allows for insulation up to 2 inches. The unique molded-in EPDM seat liner with aluminum bronze disc is recommended for most water applications. Please refer to NIBCO technical data sheets, chemical resistance guides and

+ [more](#)**Specifications**

|                             |                                       |
|-----------------------------|---------------------------------------|
| <b>UPC Code</b>             | 039923717801                          |
| <b>Type</b>                 | Butterfly Valve                       |
| <b>Valve Size</b>           | 6 in                                  |
| <b>Material</b>             | DI Ductile Iron                       |
| <b>Description</b>          | LD20003 6 LUG BFV L/LK HNDL DUCT IRON |
| <b>Turns / Operation</b>    | Quarter-Turn                          |
| <b>Seat / Seal Material</b> | EPDM Rubber                           |
| <b>Connection Type</b>      | L - Lug                               |
| <b>Operation Type</b>       | Lever-Lock Handle                     |
| <b>Disc Material</b>        | Aluminum Bronze                       |
| <b>Weight</b>               | 25.410 lb                             |