

SPECIFICATION SHEETS

FM-MS120-LED DESIGNER SERIES FLUSH MOUNT

SPECIFICATIONS


WIRING:	Installs easily in traditional junction boxes (3" or 4").
OPTICS:	LED technology delivers 1500 lumens (12" version) and 2000 lumens (16" version).
ELECTRICAL:	Integrated LEDs are direct-AC with no external driver. For usage in interior ceiling or wall installations in residential or commercial applications.
	Ambient operating temperature: -20°C (-4°F) to +50°C (+122°F).
	Certifications: ETL and Energy Star listed to U.S. and Canadian safety standards, as well as DAMP LOCATIONS rated.
LENS:	White decorative acrylic frosted lens provides an even light distribution.

COLOR TEMPERATURE:	3K - 4K
OPERATING TEMPERATURE:	-20°C + 50°C
CRI:	80+
LUMEN OUTPUT:	1500 lumens
DIMMABLE:	No
WATTS:	20 W
LED LIFE:	50,000 hours
WARRANTY:	5 years
VOLTAGE:	120V
DIAMETER:	11.75" (298.5mm)
HEIGHT:	3.375" (85.7mm)
INTEGRATED MOTION SENSOR:	Yes
MOTION SENSOR DETECTION RANGE:	10'-15' (3m-4.5m)

APPLICATIONS

The Azure series of LED flush mount fixtures by NDR Lighting offers an affordable and stylish design that will complement a varied assortment of lighting applications. The acrylic diffuser may be easily removed for installation and cleaning. Ideal for interior ceiling or wall installations in residential or commercial applications.

DIMENSIONS



RATINGS



ORDERING GUIDE

AZURE FM-MS120 SERIES

Motion Sensor Series FM-MS120-20W Color Temperature 3K 3000K/80CRI/20W 4K 4000K/80CRI/20W Finish WH White

Notes: Configure product using BOLD options: Ex: FM-MS120-20W-3K-WH