

MO98 ZOOM SPOUT® OILER



A Paraffin Based, Non-Gumming, High Quality Lubricating Oil

- All-Purpose Lubricating Oil
- Flexible Spout Extends and Retracts, Adjusts to Any “In-Between” Length
- Withstands High Temperatures Without Breaking Down
- Viscosity 92-99 @ 140°F
- 4 oz. Bottle
- 12 Per Case

MO44 RUST BUSTER® SOLVENT



Dissolves Rust

- Telescoping Pullout Spout
- Loosens Rust in Seconds
- No Lingering Odor
- Counter Display Case
- 4 oz. Bottle
- 12 Per Case

S132 SIL GLYDE



Long Lasting, High Film Strength Lubricant for All Surfaces Including Rubber, Metal, Wood and Glass.

- Weatherproof
- -20°F to 600°F Range
- 1.5 oz. Tubes
- 12 Per Case

S8 SUPCO88 OIL ADDITIVE



Introduced in 1954 and Valued Worldwide, this Super Lubricant is a “Must Use” in Repair and Preventative Maintenance Programs

- Compatible with ALL Refrigerant Oils
- Dissolves Sludge Buildup on Bearing and Valve Surfaces
- Prevents Binding of High Speed Compressors
- Prevents Excess Wear in Motors and Compressors
- 8 oz. Bottle
- 24 Per Case

Application Notes

To Prevent Excess Wear on Expansion Valves and Capillaries Mix 1 Part SUPCO88 to 9 Parts Refrigeration Oil.

- Prevents Excess Wear on Expansion Valve Needles and Seats
- Penetrates the Pores of ALL Moving Metal Parts of the Expansion Valve for Constant Lubrication

Extend the Life of ALL Motors (i.e. for blowers and air conditioners)

- A Few Drops Will Help Free a “Frozen” or Sticking Motor Shaft
- Mix 9 to One for Regular Bearing Maintenance
- Decreases “Bearing to Shaft” Friction and Sludge Accumulation when Mixed 9 to 1

More Efficiency for High Speed Compressors

- Increases the Lubricating Capability of Mineral Oils in High Speed Compressors
- Used in New Units to Reduce Current Draw by Reducing Friction and Preventing Overloading
- SUPCO88 Can be Left in the System Permanently

HS2200 GREEN PANTABS



Economical Condensate Drain Pan Treatment

- Helps Eliminate Odors
- Prevent Overflows & Water Damage
- Non-Corrosive
- Easy to Install
- Cleans Scale & Sludge
- Non-Toxic

- Acceptable for Computer Room Use
- Suitable for Use in Humidifiers
- Ideal for Fan Coils and Window Units
- Great for Refrigerated Food Cases
- Use 2 to 4 Tablets Per Month for Every 1 Ton of Air Conditioning/Refrigeration