


RectorSeal T plus 2®

PTFE enriched pipe thread sealant



Code	Description	Qty.
23710	1-¾ oz.	24
23631	¼ pt.	24
23551	½ pt.	24
23431	1 pt.	12
23391	1 qt.	12
23271	1 gal.	4
23112	55 gal.	1

Application • Contains PTFE & synthetic fibers for superior performance • Can be pressurized immediately following application

- Recommended for**
- Galvanized Steel • Iron
 - Brass • Copper • Aluminum
 - Stainless Steel
 - Polyethylene • RTRP
 - PVC • CPVC • ABS



Also available in 55 gal. container.



FILE NO. 1282




LISTED PIPE JOINT COMPOUND MH12259

- FEATURES**
- Non-setting
 - Lead free
 - 2 year shelf life
 - Certified to NSF/ANSI 61-G & 372

RectorSeal Tru-Blu™

Vibration resistant pipe thread sealant



Code	Description	Qty.
31780	1-¾ oz.	24
31631	¼ pt.	24
31551	½ pt.	24
31431	1 pt.	12
31300	1 qt.	12

Application • For high vibration environments such as refrigeration and industrial applications • Designed for sealing vibration prone NPT connections

- Recommended for**
- Galvanized Steel • Iron
 - Brass • Copper • Aluminum
 - Stainless Steel • PVC
 - Polyethylene
 - Reinforced fiberglass



FILE NO. 1282

- FEATURES**
- Fast drying / Flexible set
 - Contains PTFE
 - Lead free
 - 2 year shelf life
 - Certified to NSF/ANSI 61-G & 372

*FBC™ System Compatible™ indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® pipe and fittings.

**FBC™, FlowGuard Gold®, BlazeMaster® and Corzan® are licensed trademarks of The Lubrizol Corporation.