# Steel City®

## **Ceiling Fan Boxes and Accessories**

# Fan and Fixture Support

## **Steel and Non-Metallic Boxes** and Bar Hangers for Fan and **Fixture Installation**

Exhaustive research and development has resulted in an innovative line of Ceiling Fan Support Boxes that give Thomas & Betts the competitive advantage. Ceiling fan and fixture installation is faster, easier and safer with Steel City® Ceiling Fan Support Boxes.

- Gold finish on ears/screws easily identifies boxes as meeting UL and NEC® requirements for fan support
- UL Listed up to 50 lbs. for fixture and 35 lbs. for fan
- Each box comes complete with instructions and installation hardware

#### **Ceiling Fan and Light Fixture Bar Hanger**

- Square end plates keep the bar parallel with sheetrock
- Square section tube is easy to grip, allowing high torque for safe installation
- UL Listed up to 50 lbs. for fixture and 35 lbs. for fan
- Expandable for joists spaced from 16 to 24 inches






(h)

the unique design of the Old-Work Bar Hanger ensures a trouble-free installation that surpasses the competition.

Intended for retrofit installations,

NEC and National Electrical Code are registered trademarks of the National Fire Protection Association, Inc.




#### Ceiling Fan Support Boxes

Max. rec. loads 35 lbs. fan and 50 lbs. fixture.

CAPACITY			DIMENSIONS (IN.)		NEW/OLD	STD.
CAT. NO.	CU. IN.	DESCRIPTION	DIA.	DEPTH	WORK	CTN.
56111-CFB	6.0	Pan type ceiling fan box with 3 x ½" KOs and non-metallic sheathed cable connector	4	1/2	Both	10
54151-CFB	15.8	$1 \mbox{$\frac{1}{2}$}"$ deep ceiling fan box with 3 x $\mbox{$\frac{1}{2}$}"$ KOs and clamps for non-metallic sheathed cable	4	1½	New	10
54151-1/2-CFB-BP	15.8	1½" deep ceiling fan box with 5 x ½" KOs. Bulk pack	4	11/2	New	50
54171-CFB	22.0	$2 \%$ deep ceiling fan box with 3 x $1\!\!/\!\!2$ KOs and clamps for non-metallic sheathed cable	4	21/8	New	10
54171-F-CFB*	22.0	As 54171-CFB, but with "F" style mounting bracket	4	21/8	New	10
54171-1/2-F-CFB-BP	22.0	$2\%$ deep ceiling fan box with 5 x $1\!\!/\!_2$ " KOs and "F" style mounting bracket	4	21/8	New	50

				KNOCKOUTS (IN.)				
CAT. NO.	CLAMPS	EARS	BRKTS.	EA. SIDE Conduit	EA. END Conduit	EA. END Cable	BOTTOM Conduit	STD. CTN.
54541-CFB	2½" DP	_	Concrete ring	1/2-3/4	_	_	_	50
54551-CFB Max. loads 35 lbs. fa	3" DP	_ _	Concrete ring	1/2-1/4	_	_	_	50



<sup>\*</sup> Maximum load for 54171-F-CFB is 70 lbs. fan and 200 lbs. fixture.







54171-CFB





54541-CFB



**United States** Tel: 901.252.8000

800.816.7809 Fax: 901.252.1354 **Technical Services** Tel: 888.862.3289



# **Ceiling Fan Boxes and Accessories**

**Extra Heavy-Duty New-Work Bar Hangers** 

# **Ceiling Fan and Light Fixture Bar Hangers**

This innovative extruded-aluminum bar hanger was designed for strength. It is UL Listed for up to 70 lbs. for fan support and an industry-leading 200 lbs. for fixture support

- Gold end plates easily identify the hanger as meeting UL and NEC<sup>®</sup> requirements for fan support
- Screwed-on end plates are consistently strong and avoid unsightly welds
- End plates feature temporary fixing spikes for hands-free installation
- Expandable for joists spaced from 16 to 24 inches





56111CFB-BHL



4070CFB-BHL



54151CFB-BHL



CFB-BHL



CAPACITY				AX. LOAD	NEW/OLD		
CAT. NO.	CU. IN.	DESCRIPTION	FAN	FIXTURE	WORK	STD. CTN.	
56111CFB-BHL	6.0	New-work bar hanger with $\frac{1}{2}$ " pan-type ceiling fan box with 3 x $\frac{1}{2}$ " KOs and non-metallic sheathed cable connector	70 lbs.	200 lbs.	New	10	
54151CFB-BHL	15.8	New-work bar hanger with 1½" deep ceiling fan box with 3 x ½" KOs and clamps for non-metallic sheathed cable	70 lbs.	200 lbs.	New	10	
4070CFB-BHL	21.5	New-work bar hanger with non-metallic ceiling fan box with clamps for non-metallic sheathed cable	35 lbs.	50 lbs.	New	10	
CFB-BHL	*	New-work bar hanger without outlet box. Mounting bracket for outlet box included	_	*	New	10	

<sup>\*</sup> Dependent on box used.

NEC and National Electrical Code are registered trademarks of the National Fire Protection Association, Inc.

800.816.7809

Fax: 901.252.1354