TITAN™ 2-VALVE TEST & CHARGING MANIFOLD °F and °C



Comes with the same features and benefits as the TITAN $^{\text{\tiny M}}$ 4-valve unit but without the fourth hose. All fittings 1/4" unless otherwise noted.

Replacement parts on page 44.

| UPC# | Description - °F/°C | Gauges | Scale | Refrigerant |
|--------|---|----------|---------|------------------|
| 49814 | Manifold only with 5/16" fittings | Red/Blue | kPa/psi | |
| 49813 | With 60" PLUS II™ 5/16x5/16" RYB | Red/Blue | kPa/psi | |
| 49815 | Manifold only with 5/16"-1/4"-5/16" | Red/Blue | kPa/psi | |
| | anchor fittings and 1/4" service fittings | | | |
| 49862 | Manifold only with 1/4" fittings | Red/Blue | bar/psi | R-32/410A |
| 49860 | With 60" PLUS II™ compact ball valve RYB | Red/Blue | bar/psi | |
| 49864 | Manifold only with 5/16" fittings | Red/Blue | bar/psi | |
| 49865 | With 60" PLUS II™ RYB | Red/Blue | bar/psi | |
| 49866 | Manifold only with 5/16"-1/4"-5/16" | | | |
| | anchor fittings and 1/4" service fittings | Red/Blue | bar/psi | |
| 49849 | With 72" PLUS II™ Acme fittings RYB | Red/Blue | psi | R-1234yf |
| UPC# | Description - °F | Gauges | Scale | Refrigerant |
| 49883 | Manifold only | Red/Blue | psi | |
| 49887 | With 60" PLUS II™ RYB | Red/Blue | psi | R-22/134a/404A |
| 49889 | With 60" PLUS II™ SealRight RYB | Red/Blue | psi | |
| 49801 | With 60" PLUS II™ SealRight RYB | Red/Blue | psi | |
| 49863 | Manifold only | Red/Blue | psi | |
| 49281* | Manifold only | Red/Blue | psi | R-22/404A/410A |
| 49867 | With 60" PLUS II™ RYB | Red/Blue | psi | |
| 49868 | With 60" PLUS II™ compact ball valve RYB | Red/Blue | psi | |
| 49832 | Manifold only | Red/Blue | psi | |
| 49835 | With 60" PLUS II™ RYB | Red/Blue | psi | R-134a/404A/407C |
| 49831 | With 60" PLUS II™ SealRight RYB | Red/Blue | psi | |
| 49847 | With 72" PLUS II™ Acme fittings RYB | Red/Blue | psi | R-12/22/134a |
| UPC# | Description - °C | Gauges | Scale | Refrigerant |
| 49816 | Manifold only | Red/Blue | bar/psi | R-12/22/502 |
| 49833 | Manifold only | Red/Blue | bar/psi | |
| 49812 | Manifold only | Red/Blue | kPa/psi | R-22/134a/404A |
| 49811 | 49812 with 60" PLUS II™ RYB | Red/Blue | kPa/psi | |
| 49836 | Manifold only | Red/Blue | bar/MPa | R-134a/404A/407C |
| 49856 | Manifold only | Red/Blue | bar/psi | D 00/4404 |
| 40922 | Manifold only with 5/16" fittings | Red/Blue | MPa | R-32/410A |



Manifold comes standard with certified gauges.

PROTECTIVE GAUGE BOOTS

For 2-1/2" (63.5 mm), 3-1/8" (80 mm), and solar gauges



Rubber boots slip easily around gauges to cushion and protect them from impact.

- Fit 2-1/2" and 3-1/8" gauges without covering easy access recalibration screw
- Color-coded red or blue to match gauge

| UPC# | Description |
|-------|-----------------------------------|
| 49090 | 2-1/2" Set of gauge boots |
| 49091 | 2-1/2" Red protective gauge boot |
| 49092 | 2-1/2" Blue protective gauge boot |
| 49190 | 3-1/8" Set of gauge boots |
| 49191 | 3-1/8" Red protective gauge boot |
| 49192 | 3-1/8" Blue protective gauge boot |
| 49087 | Red solar gauge boot |
| 49088 | Blue solar gauge boot |
| 49089 | Solar gauge boot set |

HEAVY DUTY 2-1/2" BRASS MANIFOLD GAUGES (°F and °C) With 1% accuracy (Class 1) calibration



Solid brass case and premium movements. Heavy duty phosphor bronze and stainless steel internal components for longer service life under severe use.

 Flutterless[™] technology with brass surge protector to minimize needle pulsation

- 1/8" NPT Male connection
- · Calibrated to 1% accuracy
- Full view glass crystal

| | UPC# | Description | Pressure scale | Refrigerants | | |
|---|------------------|--|----------------|------------------|--|--|
| | 49067 | °F Brass pressure | 0 - 500 psi | R-22/134a/404A | | |
| | 49068 | °F Brass compound | 30"-0-120* psi | 11-22/1044/404/4 | | |
| | 49073 | °C Brass pressure | 0 - 500 psi | R-134a/404A/407C | | |
| | 49074 | °C Brass compound | 30"-0-120* psi | | | |
| , | Certified Gauges | | | | | |
| | 49199 | 2-1/2" Brass pressure | 0 - 500 psi | R-22/134a/404A | | |
| | 49200 | 2-1/2" Brass compound | 30"-0-120* psi | | | |
| | 49010 | Replacement crystal (polycarbonate) for old 49011, 49012 | | | | |
| | 49039 | Glass crystal for brass gauge | | | | |
| | 49040 | Brass gauge ring | | | | |

*Features retard protection to 350 psi. Note: Gauges are not meant to be used with nitrogen.

PROTECTIVE GAUGE BOOTS

For 2-1/2" and 3-1/8" gauges



- Rubber boots slip easily around gauges to cushion and protect them from impact
- Fit 2-1/2" or 3-1/8" gauges without covering easy access recalibration screw
- Color-coded red or blue to match gauge

| UPC# | Description |
|-------|------------------------------------|
| 49090 | 2-1/2" Set of gauge boots |
| 49091 | 2-1/2" Red protective gauge boot |
| 49092 | 2-1/2" Blue protective gauge boot |
| 49190 | 3-1/8" Set of gauge boots |
| 49191 | 3-1/8" Red protective gauge boot |
| 49192 | 3-1/8" Blue protective gauge boot |
| 49087 | Red solar gauge boot |
| 49088 | Blue solar gauge boot |
| 49089 | Set red and blue solar gauge boots |

