

-GENESIS-

Plenum Rated Security & Control Cable Part Number: 3276

18 AWG 5 Stranded Conductors Shielded

Ratings CMP, CL3P, FPLP, FT6

Approvals ETL Listed

Construction

Conductor 18 AWG 19 Strand Bare Copper

Conductor Count 5

Insulation Plenum PVC (0.007" nom.)

Insulation Colors Black, Red, White, Green, Brown

Lay Length 3.50" nom.

Shielding Aluminum Foil/Mylar w/ 24 AWG Tinned-Copper Drain

Rip Cord Yes

Jacket Plenum PVC (0.015 " nom.)

Overall Diameter 0.197" nom.

Print Legend GENESIS P/N 3276 5C 18AWG SHIELDED 3038058 (ETL) CL3P OR FPLP OR CMP
C(ETL)US FT6 75C (RoHS) W/O# XXXXXX-XXXXXXX XXXXFT A B C D E F 1 2 3 4 5 6 7
8 9

Properties

Operating Voltage 300 Volts max.

DC Resistance 6.66 Ohms/1000' at 20°C

Capacitance 50.8 pF/ft. nom.

Impedance 36 Ohms nom.

Temperature -20°C to 75°C

Flame Rating NFPA 262 (Plenum); CSA C22.2 No. 2556 (FT6)

RoHS Compliant Yes

Country of Origin USA