

Bullet™

Stub Out & Air Chamber

- Reduce job site and shop costs such as measuring, cutting, cleaning, fluxing, assembling and soldering
- Turn your variable job site costs into fixed job costs
- 1¼" - 2" CTS Bullets available for quote
- Accepts sweat, push-fitting and compression valves

Polished Nickel-Plated

- Eliminates the need for sleeving or tinning
- Solders with standard flux and solder

Bracketed Stub Out

- Perfect for stubbing up through the floor for closets or lavs
- Square O Strap is crimped to tube 12" from each end

Item No	Copper Type	CTS	Length	Pkg	Min Qty	Case Qty
STANDARD						
622-M06	M	½"	6"	B	100	100
622-M06PK	M	½"	6"	C*	20	20
622-M08	M	½"	8"	B	100	100
622-M08PK2	M	½"	8"	C*	10	10
622-M10	M	½"	10"	B	100	100
622-M12	M	½"	12"	B	100	100
622-M12PK2	M	½"	12"	C*	10	10
622-M15	M	½"	15"	B	100	100
622-M18	M	½"	18"	B	100	100
622-M24	M	½"	24"	B	50	50
622-L06	L	½"	6"	B	100	100
622-L06PK	L	½"	6"	C*	100	100
622-L08	L	½"	8"	B	100	100
622-L08PK	L	½"	8"	C*	100	100
622-L10	L	½"	10"	B	100	100
622-L12	L	½"	12"	B	100	100
622-L15	L	½"	15"	B	100	100
622-L18	L	½"	18"	B	100	100
622-L24	L	½"	24"	B	50	50
623-L06	L	¾"	6"	B	50	50
623-L08	L	¾"	8"	B	50	50
623-L12	L	¾"	12"	B	50	50
623-L15	L	¾"	15"	B	50	50
623-L18	L	¾"	18"	B	50	50
623-L24	L	¾"	24"	B	50	50
624-L08	L	1"	8"	B	30	30
624-L12	L	1"	12"	B	30	30
624-L15	L	1"	15"	B	30	30
624-L18	L	1"	18"	B	30	30
624-L24	L	1"	24"	B	30	30
NICKEL-PLATED						
622-L08N	L	½"	8"	B	25	25
BRACKETED						
622-L24E	L	½"	24"	B	20	20



622-L08




622-L24E



622-L08N



Bullets™ save time and reduce on-the-job costs. Perfect for any stub out or air chamber application.



Leakproof

Spin closed ends have **five** times the wall thickness of the copper tube. Each fitting is factory inspected.



SUPPLY

DRAINAGE

SUPPORT

APPENDIX