Nokorode® Pre-Tinning

SPECIALTY FLUXES

Code	Description	Qty.
14115	8 oz. tool box	24

FEATURES

- · Lead free
- · Cleans, pre-tins and fluxes
- Excellent wetting ability

95/5 Paste Flux

Application • Formulated with 95/5 tin/antimony which pre-tins before wire solder is applied • Excellent for use on large diameter fittings or faster soldering of smaller diameter fittings

Recommended for • 95/5 • 50/50

 Common metals (copper, tin, zinc, nickel and sheet lead)



C-Flux®

High quality flux

Code	Description	Qty.
74026	3 oz.	48
74025	12 oz.	24

FEATURES

- Lead free
- Blend of 95/5 tin/antimony

Application • Soft soldering, multi-purpose paste that contains a blend of flux and powdered solder (95/5 tin/antimony) • Cleans, fluxes and pre tins in one operation

Recommended for

- 95/5 60/40 50/50
- 40/60 All solderable metals (copper, tin, zinc, nickel and sheet lead)



Fluxomatic[™] Gel

Instant acting flux

Code	Description	Qty.
74104	8 oz.	24

FEATURES

- Non-acid
- · No fumes or odor
- · Leaves no residue
- · Will not clog valves

Application • Prepares metals for rapid soldering in the 370°F to 550°F range Easy application assures total removal of oxide films and a joint that is completely

Recommended for • Copper • Brass

- Bronze Tin Zinc Sheet metal
- · Stainless steel · Galvanized metal
- Nickel Chrome Monel
- Ferrous metal (cast iron, iron and steel)

