

FEATURES & SPECIFICATIONS

INTENDED USE — Recessed housing rated IC or Non-IC. For new construction only.

Approved for all ceiling and wiring types.

Approved for direct burial in insulation.

CONSTRUCTION — Air-tight standard. Tested to meet current energy codes.

Aluminum housing with galvanized steel pan.

Galvanized bar hangers span up to 24" o.c. and feature stepped shank nail and positioning guide with integral T-bar locks. Two locking screws hold fixture in position.

Galvanized steel junction box with four built-in Romex clamps. Four 1/2" and two 3/4" knockouts with slots for pryout. Rated for through branch wiring.

Maximum 4 (2 in, 2 out) No. 12 AWG conductors. Rated for 90°C.

Ground wire provided.

Removable J-box doors for easy access.

ELECTRICAL — Durable medium-base porcelain socket with nickel plated copper alloy screw shell and contact.

Socket clips to top of housing to prevent paint overspray in socket screw shell.

Socket attaches to reflector to ensure proper and consistent lamp position.

Thermal protection provided against improper lamp usage.

120 volt only.

INSTALLATION — Air-tight housing suitable for air-tight installations. Refer to energy codes for proper installations.

2x8 and 2x6 wood joist or T-bar installation.

Expandable bar hangers allow for off-center mounting in wood joist or T-bar ceilings. Length of 25-1/2" maximum 13-1/4" minimum or cut to fit 5-1/2" on center joist construction.

Vertical adjustment of housing allows for flush mounting with ceiling face.

Suitable for ceilings up to 1-1/2" thick.

LISTINGS — UL Listed to US and Canadian safety standards. Damp location listing (See trim selection for wet location listing).

WARRANTY — 1-year limited warranty. Complete warranty terms located at www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Note: Actual performance may differ as a result of end-user environment and application. Specifications subject to change without notice.



Catalog Number
Notes
Type

4" Housing

L3

INCANDESCENT

IC/Non-IC
New Construction



Specifications

Height: 5-1/4 (13.3)

Length: 13-1/4 (33.7)

Width: 12-3/16 (30.9)

Ceiling opening: 4 (10.2)

All dimensions are inches (centimeters) unless otherwise specified.

ORDERING INFORMATION

For shortest lead times, configure product using **bolded options**.

Example: L3 R6

L3		
Series	Options	Packaging
L3	<u>Shipped installed in fixture</u> PHC Poke-home wire connector GSKT Foam gasketing. Aids in air-tight installation.	R6 Resale pack of six U Unit

Accessories: Order as separate catalog number.
ATK3 R6 Airtight trim kit

Notes

See trim summary on reverse side for maximum wattages.

L3 4" New Construction Housing

Description Catalog number	Maximum wattage ¹	Description Catalog number	Maximum wattage ¹	Description Catalog number	Maximum wattage ¹	Description Catalog number	Maximum wattage ¹
General/Task		Accent/Wallwash		Wet Location²			
Open Narrow Flange 301 White 301MW Matte white 301A Clear diffuse, white plastic flange 301A PFMW Clear diffuse, matte white plastic flange 301AZ Clear specular anodized 301BLZ Black specular anodized 301BN Brushed nickel 301ORB Oil-rubbed bronze		Baffle Narrow Flange 3B1 Black 3B1 TRMW Black matte, white flange 3B1BN Brushed nickel 3B1ORB Oil-rubbed bronze		Eyeball Narrow Flange 3E1 White 3E1MW Matte white 3E1BN Brushed nickel 3E1BZA Antique bronze 3E1ORB Oil-rubbed bronze		Wetlite Narrow Flange 3H20 White 3H20MW Matte white 3H20BN Brushed nickel 3H20ORB Oil-rubbed bronze	
<i>IC</i>	 30 R20 35 PAR20	<i>IC</i>	 35 PAR20 <i>Non IC</i> 50 PAR20	<i>IC</i>	 50 PAR20 50 R20	<i>IC</i>	 75 PAR30 Short neck
<i>Non IC</i>	50 PAR20	<i>Non IC</i>	50 PAR20 50 R20	<i>Non IC</i>	50 R20 50 PAR20	Notes 1 Maximum wattage listed. Lower wattage lamps may be used. 2 Wetlite trim is wet location listed and outdoor rated. All other trims are damp location.	
Baffle Narrow Flange 3B1W White 3B1MW Matte white		Baffle Deep Narrow Flange 3B2 Black		Wallwash Narrow Flange 3W1 White			
<i>IC</i>	 50 PAR20 50 R20	<i>IC</i>	 30 R20 35 PAR20 <i>Non IC</i> 50 R20	<i>Non IC</i>	 50 R20 50 PAR20		
<i>Non IC</i>		<i>Non IC</i>		<i>Non IC</i>			
				Pinhole Narrow Flange 3S1 White			
				<i>IC</i>	 35 PAR20 <i>Non IC</i> 50 PAR20		

P Series Open and Baffle Wide Flange LED Modules (Wet Location)

5
YEAR
warranty



Center2Edge™



Example: 4BP TRMW LED 27K 90CRI
L3¹

ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Series/Finish	Lamp	CCT / CRI / W / Lumens ²	Voltage
4BPMW 4" Baffle LED module, matte white	LED	(blank) 3000 K / 83CRI / 10.6W / 620L	(blank) 120V
4BP TRMW 4" Baffle LED module, black baffle, matte white flange		27K 90CRI 2700 K / 93CRI / 11.2W / 600L	
4BPBN 4" Baffle LED module, brushed nickel		30K 90CRI 3000 K / 93CRI / 11.2W / 600L	
4BPORB 4" Baffle LED module, oil-rubbed bronze		40K 90CRI 4000 K / 92CRI / 9.9W / 650L	
40PA 4" Open LED module, clear diffuse			
40PAZ 4" Open LED module, clear specular			
40PA TRMW 4" Open LED module, clear diffuse, matte white flange			
40PAZ TRMW 4" Open LED module, clear specular, matte white flange			

Notes

- L3 must be ordered on separate line.
- Total system delivered lumens.

L3 4" New Construction Housing

LED Gimbal Module (Damp location)

5
YEAR
warranty



Example: 4G1MW LED

L3¹

ORDERING INFORMATION

For shortest lead times, configure product using **bolded options**.

4G1		LED		
Series/Finish		Lamps	CCT / CRI / W / Lumens ³	Voltage
<u>Series</u>	<u>Finish</u>	LED	(blank) 3000k / 83CRI / 7.9W / 435L	(blank) 120V
4G1	4" Gimbal module		27K 90CRI 2700K / 91CRI / 8.3W / 480L	
	MW Matte white		30K 90CRI 3000K / 93CRI / 7.7W / 500L	
	MB Matte black ²		40K 90CRI 4000K / 94CRI / 8W / 560L	
	BN Brush nickel ²			
	ORB Oil-rubbed bronze ²			

Notes

- 1 L3 must be ordered on separate line.
- 2 Available in 30K 83CRI only.
- 3 Total system delivered lumens.

E Series Baffle Wide Flange LED Modules (Wet Location)

5
YEAR
warranty



Example: 4BEMW LED

L3¹

ORDERING INFORMATION

For shortest lead times, configure product using **bolded options**.

4BEMW		LED		
Series/Finish		Lamps	CCT / CRI / W / Lumens ²	Voltage
4BEMW	4" Baffle LED module, matte white	LED	27K 2700 K / 82CRI / 10.3W / 530L	(blank) 120V
			30K 3000 K / 82CRI / 10.3W / 570L	
			40K 4000 K / 82CRI / 10.3W / 600L	
			50K 81CRI 5000K / 81CRI / 9.6W / 640L	
			27K 90CRI 2700K / 90CRI / 9.77W / 600L	
			30K 90CRI 3000K / 90CRI / 9.7W / 630L	
			40K 90CRI 4000K / 90CRI / 9.0W / 650L	

Notes

- 1 L3 must be ordered on separate line.
- 2 Total system delivered lumens.