



4700 W. 160th St.
Cleveland, OH 44135
PH:800-321-9532
FX:800-321-9535
www.oatey.com

TECHNICAL SPECIFICATION

LEVEL FIT 45° SWIVEL CLOSET FLANGE



TECHNICAL SPECIFICATION: Oatey Level Fit Offset Closet Flanges with Metal Ring are designed for where clearance doesn't allow for normal flange installation.



APPROVALS AND LISTINGS



IAPMO Listed

PHYSICAL/CHEMICAL PROPERTIES

Material/Color ABS Plastic = Black
 PVC Plastic = White

DIRECTIONS FOR USE

Punch 1-3/8" hole in metal stud. Snap clamp into hole. Clamp is offset to allow for adjustment of centers from stud to stud. 1/2" clamp allows for 1/4" and 3/8" tubing installation through secondary holes in clamp. Check with local codes to ensure proper spacing requirements for piping support.

PRECAUTIONS

Read cautions and directions on packaging carefully before using this product. KEEP OUT OF REACH OF CHILDREN.

COMMON APPLICATIONS

Oatey Metal Stud Insulating Pipe Clamps can be installed to isolate piping away from the stud and reduce water line noise and vibration in metal stud installations.

Consult Oatey Technical Department for applications not specifically referenced above.

PRODUCT NUMBER	DESCRIPTION	PACK	CARTON WEIGHT
43815	3" or 4" ABS 45° Swivel Closet Flange	6	6 lbs.
43816	3" or 4" PVC 45° Swivel Closet Flange	6	6 lbs.