

OS4600LED-2HO

High Power Twin-Head Flood



NAME:

TYPE:

DATE:

NOTES:

SPECIFICATIONS

LIGHT UNIT:

Rugged cast-aluminum, corrosion-resistant housing with dark bronze, black or white powder paint for lasting durability. LED lamp heads are thermally isolated from the driver that is located in the rear housing, promoting a long service life. Adjustable Photocell Sensitivity Adjustable brightness control allows for selectable lumen output of 4000 or 6000 lumens. Twin head lenses are sealed to keep out moisture, dirt and bugs. LEDs maintain 70% of light output at 50,000 hours of service life.

INSTALLATION:

Crossbar and hardware provided. Wet location listed for mounting 4 feet above ground. Tool-less adjustable heads allow for precise aiming. Dual mount system: Can be mounted on walls or soffits.

ELECTRICAL:

Energy efficient LED provides 4000 or 6000 lumens, consumes 43W or 65W utilizing 120-277V 60Hz driver. Selectable Color Temperature, choice of 4000K or 5000K Rated for outdoor installations, -40°C minimum ambient. LISTINGS UL/cUL listed Listed to U.S. and Canadian safety standards for wet locations.

COLOR
TEMPERATURE:

4K - 5K

CRI:

80

LUMEN OUTPUT:

4000 - 6000 lumens

WATTS:

43 Watts - 63 Watts

LED LIFE:

50,000 hrs

WARRANTY:

5 years


VOLTAGE:

120-277V

APPLICATIONS

The high performance LED oval twin-head security light offers security and general lighting for outdoor residential and commercial applications. Long lasting, energy saving illumination ideal for yards, driveways, walkways, lots and loading areas.

DIMENSIONS



ORDERING GUIDE

OS4600LED-2HO

High Power Twin-Head Flood

TRITON

Series	Color Temperature	Finish
OS4600LED-2HO	4000K-5000K/80CRI/63W	BK Black
	4000K-5000K/80CRI/63W	DB Dark Bronze
	4000K-5000K/80CRI/63W	WH White

Notes: Configure product using **BOLD** options: Ex: **OS4600LED-2HO-BK**