



SUBMITTAL INFORMATION

Iron Service Saddles - (F202-xxx-TAP style)



F202 DOUBLE STRAP IRON SERVICE SADDLES FOR DUCTILE IRON AND A/C PIPE



NOM. PIPE SIZE	O.D. RANGE (IN.)	APPROX. WT. LBS.	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
2"	2.35 - 2.50	2.8	F202-250-TAP	
2-1/2"	2.75 - 2.90	2.8	F202-290-TAP	
3"	*3.46 - 3.80	4.8	F202-380-TAP	
	*3.80 - 4.25	5.5	F202-425-TAP	
4"	**4.26 - 4.80	5.4	F202-480-TAP	
	▲ 4.74 - 5.00	5.4	F202-500-TAP	
	*4.74 - 5.26	5.4	F202-526-TAP	
6"	▲ 4.97 - 5.26	5.4	F202-526-TAP	
	5.94 - 6.69	6.5	F202-669-TAP	
	6.63 - 6.90	6.5	F202-690-TAP	
8"	6.84 - 7.60	6.8	F202-760-TAP	
	7.93 - 8.71	7.4	F202-871-TAP	
	8.63 - 9.05	7.4	F202-905-TAP	
10"	8.99 - 9.79	8.2	F202-979-TAP	
	10.00 - 10.75	10.4	F202-1075-TAP	
	10.75 - 11.10	11.5	F202-1110-TAP	
12"	11.10 - 12.12	11.5	F202-1212-TAP	
	12.00 - 12.75	12.5	F202-1275-TAP	
	12.75 - 13.20	12.5	F202-1320-TAP	
14"	13.20 - 14.38	12.5	F202-1438-TAP	
	15.30 - 16.25	16.0	F202-1625-TAP	
	16.30 - 17.25	16.5	F202-1725-TAP	
16"	17.40 - 18.40	17.0	F202-1840-TAP	
	18.50 - 19.25	17.3	F202-1925-TAP	
18"	19.50 - 20.50	20.8	F202-2050-TAP	
	21.20 - 22.20	21.3	F202-2220-TAP	
20"	22.50 - 23.50	24.0	F202-2350-TAP	
	23.80 - 24.80	24.5	F202-2480-TAP	
24"	25.60 - 26.50	31.7	F202-2650-TAP	
	31.74 - 32.74	42.0	F202-3274-TAP	

OUTLET TAP CODE		
CC (AWWA) THREAD		
THREAD	CODE NUMBER	✓ SUBMITTED ITEM(S)
3/4" CC	CC3	
1" CC	CC4	
1-1/4" CC	Δ CC5	
1-1/2" CC	CC6	
2" CC	CC7	
IP THREAD		
THREAD	CODE NUMBER	✓ SUBMITTED ITEM(S)
1/2" IP	Δ IP1	
3/4" IP	IP3	
1" IP	IP4	
1-1/4" IP	Δ IP5	
1-1/2" IP	IP6	
2" IP	IP7	
2-1/2" IP	IP8	

Δ Contact factory for availability

* Saddles for this pipe range are not available with 2" CC (CC7) or 2-1/2" IP (IP8) threads.

** These saddles with 2" CC (CC7) or 2-1/2" IP (IP8) taps only fit 4.80" O.D. pipe.

Example: F202-480-CC7 fits 4.80 pipe O.D. only

▲ This saddle is only available with 2" CC (CC7) or 2-1/2" IP (IP8) taps

FEATURES

- Body made of high strength ductile iron per ASTM A536
- Straps are 5/8" AISI C1010 steel, zinc plated with trivalent seal. Each strap has a 5/8" flat bearing surface. For saddles 3" or smaller, straps are 1/2"
- Gasket is EPDM rubber per ASTM D2000
- Finish on saddle body is fusion-bonded epoxy coating
- Certified to ANSI/NSF Standard 61
- Rated for the lesser of 350 psi on sizes 2"-12", 250 psi on sizes 14"-30", or the pressure of the pipe on which it is installed
- Conforms to AWWA C800

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

08/08/22

Submitted By: