Engineering Specification

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative
_	

CO-200-RX

Floor Cleanout with Heavy Duty Round Top

Specification

Watts CO-200-RX epoxy coated cast iron floor cleanout with 5"(127) round adjustable gasketed heavy duty nickel bronze top, removable gas tight gasketed brass cleanout plug, and no hub (standard) outlet.

Pipe Sizing		
Suffix	Description	
2	2"(51) Pipe Size	
3	3"(76) Pipe Size	
4	4"(102) Pipe Size	

Outlet Type		
Suffix	Description	
NH	No Hub (MJ)	
Р	Push On	
Х	Inside Caulk	

Options		
Suffix	Description	
-C	Membrane Clamp	
-6	Vandal Proof	
-13	Galvanized Body	

Optional Body Material		
Suffix Description		
-60	PVC Body w/Poly Plug	
-61	ABS Body w/Poly Plug	






Chart A

Pipe Size	NH	Push-On	PVC/ABS
2"(51)	4 3/4"(121)	5 1/2"(140)	4"(102)
3"(76)	4 3/4"(121)	5 1/2"(140)	4"(102
4"(102)	4 3/4"(121)	5 1/2"(140)	4"(102)

NOTICE

The load classifications are in accordance with the American National Standards ASME A112.21.1M ASME Ratings are as follows:

XHD - Safe Live Load 7500-10,000 lbs. (3375-4500 kg) The above categories are given as a guide only. Please consult factory.

NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

