



Model: \_\_\_\_\_ Item #: \_\_\_\_\_ Date: \_\_\_\_\_

Project: \_\_\_\_\_ Qty: \_\_\_\_\_ Approved By: \_\_\_\_\_

# Gas Connector Kit 9

Gas Connectors



## Standard Features

- For use with stationary and caster-mounted commercial kitchen equipment
- Male NPT End fittings rotate 360
- Heavy duty stainless steel corrugated tubing for flexibility
- Heavy duty stainless steel radial wrap prevents hose from stretching
- PVC Protective coating with anti-microbial agent for easy cleaning
- Welded construction for added durability
- For Indoor Use Only

## Specifications

|              |                               |
|--------------|-------------------------------|
| Pressure     | ▪ 1/2 psi                     |
| End Fittings | ▪ Carbon Steel, Chrome Plated |
| Tubing       | ▪ Stainless Steel 304         |
| Braiding     | ▪ Stainless Steel 304         |

## Includes:

| No. | Name                  | Description   |
|-----|-----------------------|---|
| 1   | Gas Connector         | For stationary and caster-mounted kitchen equipment.                              |
| 2   | Quick Disconnect      | Easily disconnects gas hose to move equipment for maintenance and cleaning.       |
| 3   | Shut-off Valve        | Required by code to allow manual shutoff within 6 ft. of appliance.               |
| 4   | Restraining Cable Kit | Prevents hose from being pulled too far. Includes mounting hardware.              |
| 5   | (2) 90° Elbows        | Gives versatility during installation.  |
| 6   | SwivelKing™           | Stainless steel construction with dual 360° rotation significantly reduces stress |

Visit [krowne.com](http://krowne.com) for complete replacement parts.

## Product Compliance

- ANSI Z21.41-2014 • CSA 6.9-2014 Quick Disconnect Devices For Use With Gas Fuel Appliances
- ANSI Z21.69-2009 • CSA 6.16-2009 Connectors For Moveable Gas Appliances
- ANSI Z21.69a-2012 • CSA 6.16a-2012 Addenda

| Model No. | Interior Size | Length | BTU/hr |
|-----------|---------------|--------|--------|
| M5024K9   | 1/2"          | 24"    | 87K    |
| M5036K9   | 1/2"          | 36"    | 77K    |
| M5048K9   | 1/2"          | 48"    | 68K    |
| M5060K9   | 1/2"          | 60"    | 60K    |
| M5072K9   | 1/2"          | 72"    | 55K    |
| M7524K9   | 3/4"          | 24"    | 232K   |
| M7536K9   | 3/4"          | 36"    | 218K   |
| M7548K9   | 3/4"          | 48"    | 180K   |
| M7560K9   | 3/4"          | 60"    | 158K   |
| M7572K9   | 3/4"          | 72"    | 139K   |
| M10024K9  | 1"            | 24"    | 414K   |
| M10036K9  | 1"            | 36"    | 379K   |
| M10048K9  | 1"            | 48"    | 334K   |
| M10060K9  | 1"            | 60"    | 294K   |
| M10072K9  | 1"            | 72"    | 279K   |
| M12524K9  | 1-1/4"        | 24"    | 699K   |
| M12536K9  | 1-1/4"        | 36"    | 615K   |
| M12548K9  | 1-1/4"        | 48"    | 541K   |
| M12560K9  | 1-1/4"        | 60"    | 476K   |
| M12572K9  | 1-1/4"        | 72"    | 419K   |

**WARNING:** Restraining Kits are required by law for all moveable gas equipment  
California Proposition 65 Warning

