

LIQUID DRAIN OPENER

963-HTL SERIES

Floweasy™

SPECIFICATION

Floweasy is a professional strength liquid drain opener manufactured by Hi-Tec Laboratories. Floweasy is extremely fast and effective at safely dissolving clogs in drains, sinks and toilets. Floweasy can be poured into standing water and will not harm metal, PVC pipe or septic tanks.

MATERIAL

94% virgin sulfuric acid and 12 buffers/inhibitors

INSTALLATION

Pour Floweasy directly into the standing water or drain. When using Floweasy in a toilet, put 2 ounces in first to pre-heat the toilet, wait a few minutes then add no more than an additional 18 ounces of Floweasy. Allow product to stand in drains and toilets for 15 minutes then flush for 5 minutes with cold water. Always wear rubber gloves and eye protection while using Floweasy drain opener. Material Safety Data Sheets are available in the technical documents section on our Tomahawk website.

ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____



963-HTL-FE32

Made In USA

Select Item Number

- 963-HTL-FE20 = Floweasy 20 ounce bottle
- 963-HTL-FE32 = Floweasy 32 ounce bottle
- 963-HTL-FE64 = Floweasy ½ gallon bottle
- 963-HTL-FE128 = Floweasy 1 gallon bottle

