

Job Name:

Engineer/Architect:

Job Location:

Wholesaler:

Submittal Date:

Contractor:

## CSSL 1/4" ID (3/8" OD) Coated Gas Appliance Connectors

**Use:** For use with indoor and outdoor connections of gas appliances to gas piping system. May be used with natural, manufactured, mixed and liquefied petroleum (LP or propane) gases and LP gas-air mixtures


### Design Features:

- **Superior corrosion resistance** to harsh chemicals found in most common household cleaning, plumbing repair, and masonry products when compared with uncoated gas connectors
- **UV rays and salt resistant**, ProCoat® connectors are certified for indoor and outdoor use
- **Strong and flexible** with greater depth and number of corrugations to withstand greater torque & bend cycles
- **Meets industry standards for torsion** without compromising the integrity of the coating or connector
- **Meets industry standard for repeated bending** without compromising the integrity of the coating or connector
- **One-piece construction** has no soldered or brazed joints
- **Smoother, burnished flare** on connector ends seal with less torque
- **Uniform coat over entire length of connector** for complete corrosion resistance of the stainless steel core
- **100% leak tested**

### Operating Specifications:

**Temperature:** -40° to 150° F

**Pressure:** standard line pressures up to 1/2 PSI maximum



### CONNECTOR FLOW CAPACITY (Straight Length)

	12"	18"	24"	30"	36"	48"	60"	72"
BTU per Hour (NG)	48,000	43,800	40,000	36,400	33,400	28,300	24,900	23,100
BTU per Hour (LPG)	76,800	70,080	64,000	58,240	53,440	45,280	39,840	36,960
Watts per Hour (NG)	14,067	12,837	11,723	10,668	9,789	8,294	7,297	6,770

### CONNECTOR MATERIAL SPECIFICATIONS

<b>Tubing</b>	Stainless steel
<b>Coating</b>	Polymer blend
<b>Nuts</b>	Steel, plated
<b>Fittings</b>	Steel, plated

This specification and all information contained herein is the confidential and exclusive property of Brasscraft Manufacturing Company, and shall not be disclosed to others without the written consent of Brasscraft Mfg. Co. This specification must be returned to Brasscraft Mfg. Co. if requested.

300.04 CSSL 3/8 OD Coated Gas Connectors REV 9.19

**BrassCraft®**

©2019 Brasscraft Manufacturing Company

# CSSL 1/4" ID (3/8" OD) Coated Gas Appliance Connectors

## Connectors with Fittings (con't)

<input type="checkbox"/>	CSSL44-12	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 12" length
<input type="checkbox"/>	CSSL11-12	1/4" ID (3/8" OD) with 3/4" MIP x 3/4" MIP fittings x 12" length
<input type="checkbox"/>	CSSL11-18	1/4" ID (3/8" OD) with 3/4" MIP x 3/4" MIP fittings x 18" length
<input type="checkbox"/>	CSSL11-24	1/4" ID (3/8" OD) with 3/4" MIP x 3/4" MIP fittings x 24" length
<input type="checkbox"/>	CSSL11-30	1/4" ID (3/8" OD) with 3/4" MIP x 3/4" MIP fittings x 30" length
<input type="checkbox"/>	CSSL11-36	1/4" ID (3/8" OD) with 3/4" MIP x 3/4" MIP fittings x 36" length
<input type="checkbox"/>	CSSL11-48	1/4" ID (3/8" OD) with 3/4" MIP x 3/4" MIP fittings x 48" length
<input type="checkbox"/>	CSSL11-60	1/4" ID (3/8" OD) with 3/4" MIP x 3/4" MIP fittings x 60" length
<input type="checkbox"/>	CSSL11-72	1/4" ID (3/8" OD) with 3/4" MIP x 3/4" MIP fittings x 72" length
<input type="checkbox"/>	CSSL44-18	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 18" length
<input type="checkbox"/>	CSSL44-24	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 24" length
<input type="checkbox"/>	CSSL44-30	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 30" length
<input type="checkbox"/>	CSSL44-36	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 36" length
<input type="checkbox"/>	CSSL44-36 P	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 36" length, bagged
<input type="checkbox"/>	CSSL44-48	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 48" length
<input type="checkbox"/>	CSSL44-48 P	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 48" length, bagged
<input type="checkbox"/>	CSSL44-60	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 60" length
<input type="checkbox"/>	CSSL44-60 P	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 60" length, bagged
<input type="checkbox"/>	CSSL44-72	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 72" length
<input type="checkbox"/>	CSSL44-72 P	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 72" length, bagged
<input type="checkbox"/>	CSSL47-18	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" MIP fittings x 18" length
<input type="checkbox"/>	CSSL47-24	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" MIP fittings x 24" length
<input type="checkbox"/>	CSSL47-30	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" MIP fittings x 30" length
<input type="checkbox"/>	CSSL47-36	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" MIP fittings x 36" length
<input type="checkbox"/>	CSSL77-12	1/4" ID (3/8" OD) with 3/8" MIP x 3/8" MIP fittings x 12" length
<input type="checkbox"/>	CSSL77-18	1/4" ID (3/8" OD) with 3/8" MIP x 3/8" MIP fittings x 18" length
<input type="checkbox"/>	CSSL77-24	1/4" ID (3/8" OD) with 3/8" MIP x 3/8" MIP fittings x 24" length
<input type="checkbox"/>	CSSL77-30	1/4" ID (3/8" OD) with 3/8" MIP x 3/8" MIP fittings x 30" length
<input type="checkbox"/>	CSSL77-36	1/4" ID (3/8" OD) with 3/8" MIP x 3/8" MIP fittings x 36" length
<input type="checkbox"/>	CSSL77-48	1/4" ID (3/8" OD) with 3/8" MIP x 3/8" MIP fittings x 48" length
<input type="checkbox"/>	CSSL48-12	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" FIP fittings x 12" length
<input type="checkbox"/>	CSSL48-18	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" FIP fittings x 18" length
<input type="checkbox"/>	CSSL48-24	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" FIP fittings x 24" length
<input type="checkbox"/>	CSSL48-30	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" FIP fittings x 30" length
<input type="checkbox"/>	CSSL48-36	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" FIP fittings x 36" length
<input type="checkbox"/>	CSSL48-48	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" FIP fittings x 48" length
<input type="checkbox"/>	CSSL48-60	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" FIP fittings x 60" length
<input type="checkbox"/>	CSSL48-72	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" FIP fittings x 72" length
<input type="checkbox"/>	CSSL55-12	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" FIP fittings x 12" length
<input type="checkbox"/>	CSSL55-18	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" FIP fittings x 18" length
<input type="checkbox"/>	CSSL55-24	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" FIP fittings x 24" length
<input type="checkbox"/>	CSSL55-30	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" FIP fittings x 30" length
<input type="checkbox"/>	CSSL55-36	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" FIP fittings x 36" length
<input type="checkbox"/>	CSSL55-48	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" FIP fittings x 48" length
<input type="checkbox"/>	CSSL58-48	1/4" ID (3/8" OD) with 1/2" FIP x 3/8" FIP fittings x 48" length
<input type="checkbox"/>	CSSL58-48 P	1/4" ID (3/8" OD) with 1/2" FIP x 3/8" FIP fittings x 48" length, bagged
<input type="checkbox"/>	CSSL88-12	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" FIP fittings x 12" length
<input type="checkbox"/>	CSSL88-12 X	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" FIP fittings x 12" length, bagged, cut case
<input type="checkbox"/>	CSSL88-18	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" FIP fittings x 18" length

*This specification and all information contained herein is the confidential and exclusive property of Brasscraft Manufacturing Company, and shall not be disclosed to others without the written consent of Brasscraft Mfg. Co. This specification must be returned to Brasscraft Mfg. Co. if requested.*

# CSSL 1/4" ID (3/8" OD) Coated Gas Appliance Connectors

## Connectors with Fittings (con't)

<input type="checkbox"/>	CSSL88-24	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" FIP fittings x 24" length
<input type="checkbox"/>	CSSL88-24 K12	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" FIP fittings x 24" length, 12 per carton
<input type="checkbox"/>	CSSL88-30 K12	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" FIP fittings x 30" length, 12 per carton
<input type="checkbox"/>	CSSL88-36	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" FIP fittings x 36" length
<input type="checkbox"/>	CSSL88-48	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" FIP fittings x 48" length
<input type="checkbox"/>	CSSL88-60	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" FIP fittings x 60" length
<input type="checkbox"/>	CSSL54-12	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 12" length
<input type="checkbox"/>	CSSL54-12 P	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 12" length, bagged
<input type="checkbox"/>	CSSL54-18	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 18" length
<input type="checkbox"/>	CSSL54-18 P	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 18" length, bagged
<input type="checkbox"/>	CSSL54-18 X	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 18" length, bagged, cut case
<input type="checkbox"/>	CSSL54-24	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 24" length
<input type="checkbox"/>	CSSL54-24 P	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 24" length, bagged
<input type="checkbox"/>	CSSL54-24 X	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 24" length, bagged, cut case
<input type="checkbox"/>	CSSL54-24 X10	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 24" length, bagged, carton of 10
<input type="checkbox"/>	CSSL54-30	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 30" length
<input type="checkbox"/>	CSSL54-30 P	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 30" length, bagged
<input type="checkbox"/>	CSSL54-30 X	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 30" length, bagged, cut case
<input type="checkbox"/>	CSSL54-36	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 36" length
<input type="checkbox"/>	CSSL54-36 P	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 36" length, bagged
<input type="checkbox"/>	CSSL54-36 X	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 36" length, bagged, cut case
<input type="checkbox"/>	CSSL54-48	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 48" length
<input type="checkbox"/>	CSSL54-48 P	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 48" length, bagged
<input type="checkbox"/>	CSSL54-48 X	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 48" length, bagged, cut case
<input type="checkbox"/>	CSSL54-60	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 60" length
<input type="checkbox"/>	CSSL54-60 P	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 60" length, bagged
<input type="checkbox"/>	CSSL54-72	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 72" length
<input type="checkbox"/>	CSSL54-72 P	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 72" length, bagged
<input type="checkbox"/>	CSSL57-12	1/4" ID (3/8" OD) with 1/2" FIP x 3/8" MIP fittings x 12" length
<input type="checkbox"/>	CSSL57-18	1/4" ID (3/8" OD) with 1/2" FIP x 3/8" MIP fittings x 18" length
<input type="checkbox"/>	CSSL57-24	1/4" ID (3/8" OD) with 1/2" FIP x 3/8" MIP fittings x 24" length
<input type="checkbox"/>	CSSL57-30	1/4" ID (3/8" OD) with 1/2" FIP x 3/8" MIP fittings x 30" length
<input type="checkbox"/>	CSSL57-36	1/4" ID (3/8" OD) with 1/2" FIP x 3/8" MIP fittings x 36" length
<input type="checkbox"/>	CSSL57-36 P	1/4" ID (3/8" OD) with 1/2" FIP x 3/8" MIP fittings x 36" length, bagged
<input type="checkbox"/>	CSSL57-48	1/4" ID (3/8" OD) with 1/2" FIP x 3/8" MIP fittings x 48" length
<input type="checkbox"/>	CSSL57-60	1/4" ID (3/8" OD) with 1/2" FIP x 3/8" MIP fittings x 60" length
<input type="checkbox"/>	CSSL87-12	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 12" length
<input type="checkbox"/>	CSSL87-18	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 18" length
<input type="checkbox"/>	CSSL87-18 P	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 18" length, bagged
<input type="checkbox"/>	CSSL87-24	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 24" length
<input type="checkbox"/>	CSSL87-24 P	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 24" length, bagged
<input type="checkbox"/>	CSSL87-24 X10	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 24" length, bagged, cut case of 10
<input type="checkbox"/>	CSSL87-30	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 30" length
<input type="checkbox"/>	CSSL87-36	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 36" length
<input type="checkbox"/>	CSSL87-36 P	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 36" length, bagged

*This specification and all information contained herein is the confidential and exclusive property of Brasscraft Manufacturing Company, and shall not be disclosed to others without the written consent of Brasscraft Mfg. Co. This specification must be returned to Brasscraft Mfg. Co. if requested.*

# CSSL 1/4" ID (3/8" OD) Coated Gas Appliance Connectors

## Connectors with Fittings (con't)

<input type="checkbox"/>	CSSL87-36 X	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 48" length, bagged, cut case
<input type="checkbox"/>	CSSL87-48	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 48" length
<input type="checkbox"/>	CSSL87-48 P	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 48" length, bagged
<input type="checkbox"/>	CSSL87-60	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 60" length
<input type="checkbox"/>	CSSL87-60 P	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 60" length, bagged
<input type="checkbox"/>	CSSL87-72 P	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 72" length, bagged


## Connectors with Fitting & Gas Ball Valve

<input type="checkbox"/>	CSSL4M-12	1/4" ID (3/8" OD) with 1/2" MIP fitting x 1/2" FIP ball valve x 12" length
<input type="checkbox"/>	CSSL4M-18	1/4" ID (3/8" OD) with 1/2" MIP fitting x 1/2" FIP ball valve x 18" length
<input type="checkbox"/>	CSSL4M-24	1/4" ID (3/8" OD) with 1/2" MIP fitting x 1/2" FIP ball valve x 24" length
<input type="checkbox"/>	CSSL4M-30	1/4" ID (3/8" OD) with 1/2" MIP fitting x 1/2" FIP ball valve x 30" length
<input type="checkbox"/>	CSSL4M-36	1/4" ID (3/8" OD) with 1/2" MIP fitting x 1/2" FIP ball valve x 36" length
<input type="checkbox"/>	CSSL4M-48	1/4" ID (3/8" OD) with 1/2" MIP fitting x 1/2" FIP ball valve x 48" length
<input type="checkbox"/>	CSSL4M-60	1/4" ID (3/8" OD) with 1/2" MIP fitting x 1/2" FIP ball valve x 60" length
<input type="checkbox"/>	CSSL4M-72	1/4" ID (3/8" OD) with 1/2" MIP fitting x 1/2" FIP ball valve x 72" length
<input type="checkbox"/>	CSSL7M-12	1/4" ID (3/8" OD) with 3/8" MIP fitting x 1/2" FIP ball valve x 12" length
<input type="checkbox"/>	CSSL7M-18	1/4" ID (3/8" OD) with 3/8" MIP fitting x 1/2" FIP ball valve x 18" length
<input type="checkbox"/>	CSSL7M-24	1/4" ID (3/8" OD) with 3/8" MIP fitting x 1/2" FIP ball valve x 24" length
<input type="checkbox"/>	CSSL7M-30	1/4" ID (3/8" OD) with 3/8" MIP fitting x 1/2" FIP ball valve x 30" length
<input type="checkbox"/>	CSSL7M-36	1/4" ID (3/8" OD) with 3/8" MIP fitting x 1/2" FIP ball valve x 36" length
<input type="checkbox"/>	CSSL7M-48	1/4" ID (3/8" OD) with 3/8" MIP fitting x 1/2" FIP ball valve x 48" length
<input type="checkbox"/>	CSSL5M-36	1/4" ID (3/8" OD) with 1/2" FIP fitting x 1/2" FIP ball valve x 36" length
<input type="checkbox"/>	CSSL8M-12	1/4" ID (3/8" OD) with 3/8" FIP fitting x 1/2" FIP ball valve x 12" length
<input type="checkbox"/>	CSSL8M-18	1/4" ID (3/8" OD) with 3/8" FIP fitting x 1/2" FIP ball valve x 18" length
<input type="checkbox"/>	CSSL8M-24	1/4" ID (3/8" OD) with 3/8" FIP fitting x 1/2" FIP ball valve x 24" length
<input type="checkbox"/>	CSSL8M-36	1/4" ID (3/8" OD) with 3/8" FIP fitting x 1/2" FIP ball valve x 36" length
<input type="checkbox"/>	CSSL8M-48	1/4" ID (3/8" OD) with 3/8" FIP fitting x 1/2" FIP ball valve x 48" length
<input type="checkbox"/>	CSSL8M-48 P	1/4" ID (3/8" OD) with 3/8" FIP fitting x 1/2" FIP ball valve x 48" length, bagged

## Connectors Less Fittings (Connectors without fittings are NOT CSA design-certified)

<input type="checkbox"/>	CSSLNN-10N	1/4" ID (3/8" OD) x 10" length, no fittings
<input type="checkbox"/>	CSSLNN-16N	1/4" ID (3/8" OD) x 16" length, no fittings
<input type="checkbox"/>	CSSLNN-22N	1/4" ID (3/8" OD) x 22" length, no fittings
<input type="checkbox"/>	CSSLNN-28N	1/4" ID (3/8" OD) x 28" length, no fittings
<input type="checkbox"/>	CSSLNN-34N	1/4" ID (3/8" OD) x 34" length, no fittings
<input type="checkbox"/>	CSSLNN-46N	1/4" ID (3/8" OD) x 46" length, no fittings
<input type="checkbox"/>	CSSLNN-58N	1/4" ID (3/8" OD) x 58" length, no fittings
<input type="checkbox"/>	CSSLNN-70N	1/4" ID (3/8" OD) x 70" length, no fittings

# CSSL 1/4" ID (3/8" OD) Coated Gas Appliance Connectors



## PART DIMENSIONS (Inches)

### Connector Length – Nut by Nut

Model	DIM.	12"	18"	24"	30"	36"	48"	60"	72"
CSSL	A	10.50 / 11.25	16.50 / 17.25	22.50 / 23.25	28.50 / 29.75	34.50 / 35.75	46.50 / 48.75	58.50 / 60.25	70.50 / 72.25

## PART DIMENSIONS (Inches)

### Connector Lengths – with Fittings

Model	DIM.	12"	18"	24"	30"	36"	48"	60"	72"
CSSL44	B	13.00 / 13.75	19.00 / 19.75	25.00 / 25.75	30.00 / 32.25	37.00 / 38.25	49.00 / 51.25	61.00 / 62.75	73.00 / 74.75
CSSL47	B	12.75 / 13.50	18.75 / 19.50	24.75 / 25.50	29.75 / 32.00	36.75 / 38.00	48.75 / 51.00	60.75 / 62.50	72.75 / 74.50
CSSL77	B	12.50 / 13.25	18.50 / 19.25	24.50 / 25.25	30.50 / 31.75	36.50 / 37.75	48.50 / 50.75	60.50 / 62.25	72.50 / 74.25
CSSL48	B	12.60 / 13.35	18.60 / 19.35	24.60 / 25.35	30.60 / 31.85	36.60 / 37.85	48.60 / 50.85	60.60 / 62.35	72.60 / 74.35
CSSL55	B	12.34 / 13.09	18.34 / 19.09	24.34 / 25.09	30.34 / 31.59	36.34 / 37.59	48.34 / 50.59	60.34 / 62.09	72.34 / 74.09
CSSL88	B	12.20 / 12.95	18.20 / 18.95	24.20 / 24.95	30.20 / 31.45	36.20 / 37.45	48.20 / 50.45	60.20 / 61.95	72.20 / 73.95
CSSL54	B	12.67 / 13.42	18.67 / 19.42	24.67 / 25.42	30.67 / 31.92	36.67 / 37.92	48.67 / 50.92	60.67 / 62.42	72.67 / 74.42
CSSL87	B	12.35 / 13.10	18.35 / 19.10	24.35 / 25.10	30.35 / 31.60	36.35 / 37.60	48.35 / 50.60	60.35 / 62.10	72.35 / 74.10

### Connector Lengths – with Fitting & Gas Ball Valves

CSSL4M	B	13.63 / 14.38	19.63 / 20.38	25.63 / 26.38	31.63 / 32.88	37.63 / 38.88	49.63 / 51.88	61.63 / 63.38	73.63 / 75.38
CSSL7M	B	13.38 / 14.13	19.38 / 20.13	25.38 / 26.13	30.38 / 32.63	37.38 / 38.63	49.38 / 51.63	61.38 / 63.13	73.38 / 75.13
CSSL8M	B	13.23 / 13.98	19.23 / 19.98	25.23 / 25.98	30.23 / 32.48	37.23 / 38.48	49.23 / 51.48	61.23 / 62.98	73.23 / 74.98

## Listings & Certifications:

- CSA listed to ANSI Z21.24 / CSA 6.10 standard  
"Connectors for Gas Appliances"
- CSA listed to ANSI Z21.75 / CSA 6.27 standard  
"Connectors for Outdoor Gas Appliances & Manufactured Homes"



This specification and all information contained herein is the confidential and exclusive property of Brasscraft Manufacturing Company, and shall not be disclosed to others without the written consent of Brasscraft Mfg. Co. This specification must be returned to Brasscraft Mfg. Co. if requested.

300.04 CSSL 3/8 OD Coated Gas Connectors REV 9.19

**BrassCraft®**

©2019 Brasscraft Manufacturing Company