



SUBMITTAL INFORMATION

Uni-Flange® Restraint - (UFR1390-S-x-U style)




SERIES 1390-S RESTRAINT HARNESS FOR STEEL SIZE PVC PIPE BELL JOINTS CAST SIZES 4" - 12"

1300 SPLIT RESTRAINT



1390 ASSEMBLY



NOM PIPE SIZE	OD (IN.)	CATALOG No.	A	B APPROX.	C MAX	RESTRAINING BOLTS / RODS	CLAMPING BOLTS PER GLAND	MAX BELL CLEARANCE	APPROX. WEIGHT LBS	✓ SUBMITTED ITEMS
4"	4.50	UFR1390-S-4-U	1-1/8"	9-1/8"	15"	(2) 3/4" x 17"	(2) 5/8" x 3-1/2"	6.63"	17.0	
6"	6.63	UFR1390-S-6-U	1-1/8"	11-1/8"	15"	(2) 3/4" x 17"	(2) 5/8" x 3-1/2"	8.63"	18.5	
8"	8.63	UFR1390-S-8-U	1-1/4"	14-7/16"	15"	(2) 3/4" x 17"	(2) 3/4" x 4"	11.88"	29.0	
10"	10.75	UFR1390-S-10-U	1-3/8"	16-5/8"	22"	(4) 3/4" x 24"	(2) 7/8" x 5"	14.13"	53.0	
12"	12.75	UFR1390-S-12-U	1-3/8"	19-1/4"	22"	(4) 3/4" x 24"	(2) 7/8" x 5"	16.75"	56.5	

FEATURES

- Cast ductile iron per ASTM A536 grade 65-45-12
- Threaded rods are high strength, low alloy steel per ANSI / AWWA C111 / A21.11
- Side clamping nuts and bolts - Grade 5, zinc plated
- Rated at full-rated pressure of any class of PVC pipe, minimum 2:1 safety factor
- 360° contact and support of the pipe wall
- Black e-coat epoxy coating with painted gray top coat for identification

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com



09/01/21

Submitted By: