



The **Saniswift drain pump** is used to pump gray water away from a variety of fixtures in **residential applications**. The system is able to discharge the waste up to **14 feet vertical and/or 140 feet horizontal**.

- Discharges the waste through either a 1" or 1½" rigid pipe. A non-return valve is included on the discharge fitting assembly provided with the system.
- Has been designed with a 1½" vent connection on top of the lid. All plumbing codes require connection to a vent system. Either inlet located on top of the housing can be used for the vent or as an inlet. Please note that the vent system should be a two-way air vent as air needs to freely flow both ways. Note: The use of mechanical vents, air admittance valves or similar devices is not permitted.
- Discharges **gray water from a kitchen sink, shower, dishwasher, washing machine** (indirect connection via laundry sink). The gray water will drain into the system **via three 1½" inlets**, two low inlets (with built-in check valves) on either side of the housing and one on top of the enclosure.

## ResidentialGrade

### TECHNICAL SPECIFICATIONS

Pump type: Drain pump  
 Electrical: 120 V – 60 Hz / 4.5 Amps\* (Max)  
 Motor: 0.3 HP oil-filled thermally protected motor  
 Capacitor rating: 30 microfarad  
 Operating Temperature: 140°F Max.  
 Power cord length: 48 inches  
 Noise level: ≤ 44 dBA (Lp) (measured at 3 ft.)

