



SPECIFICATION

Furnish and install Corrugated Stainless Steel Water Heater Connectors as manufactured by LSP

DESIGN FEATURES

- Full Flow- 3/4" ID provide greater water flow with minimal restrictions.
- High quality EPDM gasket
- Lead Free, Non-toxic and sanitary
- Truly kink free
- Flexible but durable, even with multiple bends
- Tube resists work hardening, allowing for more flexibility and easier installation
- Integrated dielectric sleeve, so no dielectric union required
- Defect-free tubing (100% leak tested)
- High corrosion-resistant stainless steel

INSTRUCTIONS

1. For use with water in accessible locations only.
2. Install inlet according to manufacturer's instructions. For outlet nut, hand tighten nut plus 1/4" turn with wrench.
3. Turn water on and check for leaks. DO NOT OVER TIGHTEN or expose to harsh chemicals.
4. Inspect every six months. Do not re-use.

OPERATING SPECIFICATIONS

- Temperature: 40-180°F
- Max working pressure 125 PSI

MATERIAL SPECIFICATIONS

- Tubing: Stainless Steel
- End Connections: Brass
- Washer: High quality EPDM



3689 Arrowhead Drive, Carson City, NV 89706
 Phone (800) 854-3215 Fax (800) 243-1777

E-mail sales@lspproducts.com Website www.lspproducts.com
 Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained.

CORRUGATED STAINLESS STEEL WATER HEATER CONNECTORS
Specification Sheet

Part Number	Description	Length
WCS-112-PP*	3/4" F.I.P. x 3/4" F.I.P.	12"
WCS-118-PP*		18"
WCS-124-PP*		24"
WCS-312-PP	1" F.I.P. x 1" F.I.P.	12"
WCS-318-PP		18"
WCS-324-PP		24"
WCS-418-PP	3/4" F.I.P. x 3/4" COPPER SWEAT	18"
WCS-424-PP		24"
WCS-518-PP	3/4" UPONOR PEX x 3/4" F.I.P.	18"
WCS-524-PP		24"
WCSV-518-PP	3/4" UPONOR PEX 1/4 TURN BALL x 3/4" F.I.P	18"
WCSV-524-PP		24"
WCS-718-PP	3/4" PUSH TO CONN. x 3/4" F.I.P. NUT	18"
WCS-724-PP		24"
WCSV-718-PP	3/4" PUSH TO CONN. 1/4 TURN BALL x 3/4" F.I.P. NUT	18"
WCSV-724-PP		24"
WCS-818-PP	3/4" CRIMP PEX x 3/4" F.I.P. NUT	18"
WCS-824-PP		24"
WCSV-818-PP	3/4" CRIMP PEX 1/4 TURN BALL x 3/4" F.I.P. NUT	18"
WCSV-824-PP		24"
WSS-112-PP	3/4" F.I.P. X 3/4" F.I.P. Includes 3/4" Sweat Adapter	12"
WSS-118-PP		18"
WSS-124-PP		24"

* Designates Not Full Flow

COMPLIANCES/LISTINGS

- IAPMO listed to the Lead Free Plumbing Law File 6545,
- IAPMO Listed to NSF/ANSI 61 File N-6614
- IAPMO listed to ASME A112.18.6/CSA B125.6 File 2111



NSF/ANSI 61



Lead Free Compliant

Product Submittal	
Job Name:	
Date:	
Part Number	Quantity
Architect:	
Contractor:	