

PEX Press

Known for forward-thinking system solutions, Viega offers complete plumbing systems for potable water systems. With PEX tubing that meets the highest standards in the market, the revolutionary Viega ManaBloc, and Viega PEX Press manifolds in high-performance polymer, Viega PEX Solutions work together to save time, labor and cost. The first press system for the PEX market, Viega PEX Press fittings improve consistency and reduce installation errors with factory-attached sleeves. Available in high-performance polymer and Viega Zero Lead bronze, Viega PEX Press fittings are ideal for residential and commercial jobs. Viega also offers fittings for easy copper-to-PEX transitions, and system-matched tools and jaws make installation easy and consistent. Viega PEX Solutions also includes the versatile Viega FostaPEX multilayered tubing for plumbing and radiant heating applications, designed to be both rigid and highly flexible while holding its shape for plumbing and radiant heating applications.

FEATURES AND BENEFITS

- The original press fitting for PEX tubing
- Factory-assembled press fittings reduce installation errors on the job
- Available in sizes from 3/8" to 2"
- The only PEX fittings with the Viega Smart Connect feature
- 25-year limited warranty

CODES AND STANDARDS

- ASTM E84: Specification for Surface Burning Characteristic
- ASTM F876: Standard Specification for PEX Tubing
- ASTM F877: Standard Specification for PEX Water Distribution System
- ASTM F1807/F2159: Standard Specification for PEX Insert Fittings
- ASTM F2023: Standard Test Method for Evaluating the Oxidative Resistance of Cross-linked Polyethylene PEX Tubing and Systems to Hot Chlorinated Water
- AWWA C904: Cross-linked Polyethylene (PEX) Pressure Pipe for water service
- CAN/ULC S101: Standard Method of Test for Surface Burning Characteristics
- CAN/ULC S102.2: Standard Method of Test for Surface Burning Characteristics
- CSA International: Canadian Standard Association
- CSA B137.5: Standard Specification for PEX tubing systems in pressure applications
- IAPMO: Uniform Plumbing Code
- ICC: International Plumbing Code
- NSF/ANSI 61: Drinking Water System Components – Health Effects
- NSF/ANSI 61G: Lead Content Evaluation Procedure to meet < 0.25% average lead content
- NSF/ANSI 14: Plastics Piping System Components and Related Materials
- NSPC: National Standard Plumbing Code
- UL 1821: Thermoplastic Sprinkler Pipe and Fittings for Fire Protection Service
- D UL 263 Fire Tests of Building Construction and Materials

ZERO LEAD

References to Zero Lead throughout this publication mean product meeting the requirements of NSF 61-G through testing under NSF/ANSI Standard 372 (0.25% or less percent maximum weighted average lead content).

NOTE

A Green Dot on a Viega PEX Press fitting indicates the Smart Connect feature.



PEX press jaw Compact
 - For Ridgid compact tools, PEX tubing
 - Steel
Model 2884.7US

Press Jaws	Wt [lb]	Quantity	Part No	DG
3/8	2.434	1	56052	6
1/2	2.359	1	56053	6
3/4	1.370	1	56055	6
1	2.469	1	56056	6
1 1/4	2.664	1	56060	6
1 1/2	2.749	1	56061	6



PEX press jaw Standard
 - For Ridgid standard tools, PEX tubing
 - Steel
Model 2899.7US

Press Jaws	Wt [lb]	Quantity	Part No	DG
1/2	4.049	1	56073	6
3/4	3.744	1	56075	6
1	3.929	1	56076	6
1 1/4	4.434	1	56080	6
1 1/2	3.509	1	56081	6
2	9.312	1	56082	6



Tubing cutter
 - For PEX tubing
 - Suitable for Viega FostaPEX tubing
 Model 2805US, 2806US, 2808US
 - Steel
 - Ratcheting design
Model 2840

max d	Wt [lb]	Quantity	Part No	DG
2	1.595	1	53561	5



Tubing cutter
 - For PEX tubing
 - Plastic
Model 2889.2US

max d	Wt [lb]	Quantity	Part No	DG
1	0.351	1	21304	5



Tubing cutter
 - For PEX tubing
 - Plastic
Model V5055

max d	Wt [lb]	Quantity	Part No	DG
1 1/2	0.401	1	21307	5



Blade
 - Suitable for tubing cutter Model V5055
 - Steel
Model V5055.1

	Wt [lb]	Quantity	Part No	DG
	0.080	1	21317	5

Accessories



Viega PEX Press sleeve
 - Only for Viega PEX Press polymer fittings
 - Stainless steel
Model V5615.3

d	Wt [lb]	Quantity	Part No	DG
3/8	0.009	10	49901	6
1/2	0.012	10	49902	6
3/4	0.015	10	49903	6
1	0.025	10	49904	6
1 1/4	0.053	10	49905	6
1 1/2	0.065	10	49906	6
2	0.085	10	49607	6



Lav riser
 - Does not include lav nut Model V5089
 - Equipped with ferrule Model V5085
 - PEX
Model V5080

CTS	O.D.	L [in]	Wt [lb]	Quantity	Part No	DG
1/4	3/8	20	0.046	100	58120	2
1/4	3/8	30	0.068	100	58130	2
1/4	3/8	36	0.085	100	58136	2